



028 0096





Technical Data	
Voltage (V)	180-260
Product Wattage	96
Equivalence with incandescentq lamp(W)	768
Colour Render Index (Ra)	>Ra70
Colour Temperature (K)	4000K
Materials	Crystal + Stainless Steel + Iron
Protection Class	I
D	
Dimmable	No
DIMMable EEI	A to A ⁺⁺
EEI	A to A++
EEI Warm-up time up to 60 %of the full light output	A to A++ Instant Full Light
EEI Warm-up time up to 60 %of the full light output Luminous Flux (lm)	A to A ⁺⁺ Instant Full Light 2880
EEI Warm-up time up to 60 %of the full light output Luminous Flux (lm) Luminous Efficacy (lm/W)	A to A** Instant Full Light 2880 30
EEI Warm-up time up to 60 %of the full light output Luminous Flux (lm) Luminous Efficacy (lm/W) Rated Life (hrs)	A to A++ Instant Full Light 2880 30 30.000


Applications

· LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.

Features

- · High Lumen and CRI, Good quality & Constant Current driver.
- · High heat dissipation, low carbon and environmental protection.
- · SMD LED Lamp Base
- · Very low energy consumption

Technical Drawing



İstanbul Trakya Serbest Bölgesi Ferhatpaşa S.B. Mah. Açelya Sk. Dış Kapı: 2 İç Kapı: 301 Çatalca / İSTANBUL